

Installation Instructions

LICS-203LG

Please read carefully and save these instructions

**WARNING: ALL INSTALLATION WORK SHOULD BE DONE BY ACCREDITED PROFESSIONAL.
SHUT OFF POWER SUPPLY AT FUSE OR CIRCUIT BREAKER!**

PREPARING FOR INSTALLATION

- 1.Carefully remove all contents from the carton. See the important notes above. Shut off the power at the circuit breaker and completely remove the old fixture from the ceiling, including the old mounting plate. Remove the mounting plate assembly from the bag.
2. Mounting bracket (A) contains several pairs of threaded holes. Find the pair of holes that matches the spacing of the holes on the junction box and the fixture's canopy. One end of the threaded post (D) should be attached to the mounting bracket (A) with a washer and a hex nut (B, C) in place. Pull the house wires through the threaded post (D). Place mounting bracket (A) over the junction box. Secure mounting bracket (A) to the junction box by tightening the mounting screws (F).

ASSEMBLING THE FIXTURE

3. Pass the wires through one stem (O) /three stems (M) each side to achieve overall desired length. Next attach stem onto fixture with threaded post (P) on the fixture to secure tightly. Secure swivel post (L) to the top of the stem. Place reinforcing plate (H) inside canopy (I) and the canopy (I) over the threaded post (K) of the top rod. Lock the reinforcing plate and canopy with the wing nut (G) and threaded post (K).


CONNECTING THE WIRES

4. Strip 3/8"of insulation from the wire ends. Using wire connector (AA), connect RIBBED fixture wire to the WHITE supply wire from the junction box; connect the SMOOTH fixture wire to the BLACK supply wire. Connect the fixture ground wire and supply ground wire using a wire connector or by fastening to the ground screw (E) on the mounting bracket. Push all wire connections into the junction box.



FINISHING THE INSTALLATION


5. Raise canopy (I) to mounting bracket (B) and position threaded post (D) so that they protrude through the openings of canopy (I). Secure canopy (I) in place with ball nuts (J).
6. Secure cup (R) and glass (S) onto the socket (Q) by screwing socket ring (T) tight. Install light bulb (not included) in accordance with the fixture's specifications. Do not exceed the recommended maximum wattage.

Your installation is now complete. Turn on the power and test the fixture.



Accessory package

Ⓐ Wire connector		x3
Ⓐ Mounting bracket		x1
Ⓑ Washer	—	x1
Ⓒ Hex nut		x1
Ⓓ Threaded post		x1
Ⓔ Ground screw		x1
Ⓕ Mounting screws(#8-32*25mm)		x2
Ⓖ Ball nuts		x1



CLEANING TIPS

Treat the fixture gently! Regular cleaning will reduce the need for deep cleaning. For regular cleaning, turn off the light and wipe down the fixture with a clean lint-free cotton or microfiber cloth. Never spray cleaner directly onto the fixture. Dry with a lint-free or microfiber cloth.